

| SECTION | I 1: IDENTIFICATIO | ON OF THE MIXTUR | RE AND OF THE COMPANY | |
|--------------------------------|--|--|--|--|
| Product Identifier | GROTEK PRO-SILICATE 0-0-4 | | | |
| Product Use | Plant Fertilizer | Plant Fertilizer | | |
| Use restrictions | Do not use for pur | poses other than th | ose listed on the product label | |
| | Company Name | Name Greenstar Plant Products | | |
| Manufacturer | Address | 9430-198th Street, Langley BC Canada V1M 3C8 | | |
| Information | Phone Number | +1-604-882-7699 | | |
| | Email | info@getgreenstar.com | | |
| Emergency Phone Number | • | +1-604-882-7699 | | |
| SECTION 2: HAZARDS IDE | NTIFICATION | | | |
| | GI | HS CLASSIFICATION | ON | |
| HazCom 2012 GHS | Eye damage / Eye irritation Category 1 Skin irritation Category 2 | | | |
| WHMIS 2015 | Eye damage / Eye irritation Category 1 Skin irritation Category 2 | | | |
| HAZARD SYMBOL & SIGNAL WORD | HAZARD STATEMENTS | | PRECAUTIONARY STATEMENTS | |
| | H314: Causes serious eye damage H315: Causes skin irritation | | P280: Wear protective gloves and eye protection / face protection P264: Wash hands and exposed skin thoroughly after handling P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor P302+352: IF ON SKIN: Wash with plenty of water. P332+313: If skin irritation occurs, get medical advice / attention. P362+364: Take off contaminated clothing and wash it before reuse | |

SECTION 3: HAZARDOUS INGREDIENTS

| CAS# | Substance name | Percent |
|-----------|-----------------------------|---------|
| 1312-76-1 | Potassium silicate solution | 30% |
| 7447-40-7 | Potassium chloride | 1.5% |



GROTEK PRO-SILICATE 0-0-4

To the current knowledge of the supplier, this product contains no components or impurities, in the concentrations applicable, that are classified as hazardous to health or the environment or influence the classification of this product

SECTION 4: FIRST AID MEASURES

Description of first aid measures

| EYE CONTACT | Rinse with a large gentle stream of water for a minimum for 15 minutes. Remove contact lenses, if present and easy to do so after 5 minutes. Continue rinsing. Get immediate medical attention | | |
|--------------|---|--|--|
| SKIN CONTACT | Wash with soap and water and rinse with plenty of clean water. If irritation persists, seek medical advice/attention | | |
| INHALATION | Remove victim to fresh air. Seek medical attention. Effects may be delayed | | |
| INGESTION | If swallowed, DO NOT INDUCE VOMITING. If vomiting occurs, lean forward with head down to avoid breathing in vomit. If conscious and alert, wash out mouth and give 200 – 300 ml of water to drink. Immediately call a POISON CENTRE or doctor | | |

Most important symptoms and effects, both acute and delayed

High pH product - causes eye damage and skin irritation. Effects may be delayed and occur without the sensation of pain. Mists may be irritating to respiratory tract. If swallowed, may cause irritation to the mouth, esophagus and digestive tract

SECTION 5: FIRE FIGHTING MEASURES

| Flammable | Will not burn or support combustion. | | |
|---|--|--|--|
| Suitable extinguishing media | Use an extinguishing agent suitable for the surrounding fire. | | |
| Unsuitable extinguishing media | None known. | | |
| Hazardous Combustion Products | Oxides of carbon, potassium, and silicon, hydrogen chloride and/or chlorine gases, and other toxic and irritating fumes and gases may be formed. | | |
| Advice for fire-fighters | | | |
| Special protective equipment for firefighters | Self-contained breathing apparatus and full protective clothing should be worn when fighting chemical fires. | | |
| Special fire fighting procedures | In the event of fire, use water spray to cool closed containers and knock-down toxic gases. | | |



| GRO | TFK | PRO. | .SII | ICA' | TF I | 0-0-4 |
|------|-----|------|------|------|------|---------------|
| GIVO | | | UIL | | | J-U- T |

| SECTION 6: ACCIDENTAL REALEASE MEASURES | | | |
|--|--|--|--|
| SPILL & LEAK PROCEDURES | SPILLED MATERIAL IS VERY SLIPPERY. Wear personal protection equipment outlined in SECTION 8. Ventilate area. Adsorb spill then shovel or sweep spilled material into dry labeled containers for disposal. Avoid the generation of mists. Flush area with water after clean-up. | | |
| | Do not allow product or rinsing water to enter storm sewers, sanitary sewers, groundwater or soil. | | |
| SECTION 7: HANDLING AND STO | DRAGE | | |
| Precautions for safe handling | Avoid contact with eyes, skin and clothing. Wear personal protection equipment outlined in SECTION 8 when handling. Avoid the generation of mists. Do not use with incompatible materials (SECTION 10). Have eyewash station and shower readily available. Keep container closed when not in use. Clean up spills promptly | | |
| | Store in a cool, dry, well ventilated area. Do not store in aluminum, fiberglass, copper, brass, zinc or galvanized containers. | | |
| Conditions for safe storage, including incompatibilities | Avoid strong oxidizers. Lewis or mineral acids. Product may gel and generate heat when mixed with acid. May react with ammonium salts resulting in evolution of ammonia gas. Flammable hydrogen gas may be produced on contact with aluminum, tin, lead, and zinc. | | |
| Environmental precautions | This product is acutely toxic to aquatic life due to its low pH. Do not allow product to enter storm sewers, sanitary sewers, groundwater or soil. | | |
| SECTION 8: EXPOSURE CONTRO | OLS / PERSONAL PROTECTION | | |
| Control parameters | | | |
| Occupational exposure limits | No specific limits apply. An exposure limit of 2 mg / m2 (15 min TWA) is recommended by analogy with potassium hydroxide | | |
| Recommended monitoring procedures | Monitor workplace air quality to determine the effectiveness of the ventilation or other control measures and / or the necessity to use respiratory protective equipment | | |
| Engineering controls | Provide adequate local / general exhaust ventilation | | |
| Personal protection equipment | | | |
| Hygiene measures | Wash hands after handling, before eating, smoking and using the toilet and at the end of the work day. Ensure that eyewash stations and safety showers are close to the workstation area | | |
| Eye / Face Protection | chemical safety goggles or face shield when there is a potential for eye contact | | |



| Skin protection | | Hand protection | Wear chemi | Wear chemical gloves - Nitrile, latex or PVC | | |
|----------------------------------|-------------------|---|------------|--|-------------|--|
| | | Body protection | | eeved shirt and pants o | r coveralls | |
| Respiratory protection | | NIOSH approved respirator equipped with mist / fume cartridges when occupational limits are exceeded | | | | |
| Environmental exposure controls | | Do not allow product to enter storm sewers, sanitary sewers, groundwater or soil. | | | | |
| SECTION 9: PHY | SICAL AND CHE | MICAL PROPERTIES | | | | |
| Physical state | Liquid | Colour | NAV | Odour | NAV | |
| рН | 11.4 | Density | NAV | Solubility in water | Soluble | |
| Specific gravity | NAV | Melting point | NAV | Decomposition temperature | NAV | |
| Flammable? | Not flammable | Boiling point | NAV | Viscosity | NAV | |
| SECTION 10: STA | ABILITY AND RE | ACTIVITY | | | | |
| Reactivity | | Reacts with aluminum, zinc, tin and their alloys to create hydrogen gas which may form an explosive mixture with air. May react violently on contact with acids. Reacts with sugar residues to form carbon monoxide | | | | |
| Chemical stability | | Stable under normal conditions of use and storage | | | | |
| Conditions to avoid | | Do not mix with acids or ammonia salts. Avoid the generation of mists | | | | |
| Incompatibility | | See Reactivity section | | | | |
| Hazardous decomposition products | | Oxides of carbon, potassium, and silicon, hydrogen chloride and/or chlorine gases, and other toxic and irritating fumes and gases may be formed. | | | | |
| SECTION 11: TO | KICOLOGICAL II | NFORMATION | | | | |
| Information on To | oxicological effe | ects | | | | |
| Acute Toxicity | | Product is not acutely toxic | | | | |
| Irritation/ Corrosion | | Corrosive to eyes and irritating to skin, digestive and respiratory tracts. Effects are due to the high pH of the product | | | | |
| Sensitization | | Does not meet criteria | | | | |
| Carcinogenicity | | Ingredients not listed as carcinogens by ACGIH, IARC, or NTP | | | | |
| Mutagenicity | | NAV | | | | |
| Reproductive toxicity | | NAV | | | | |
| Repeated dose toxicity | | NAV | | | | |



GROTEK PRO-SILICATE 0-0-4

SECTION 12: ECOLOGICAL INFORMATION

Potassium Silicate: The Ecotoxicity of this product has not been tested. The following data is reported for chemically similar sodium silicates on a 100% solids basis: 96 hour median tolerance:

- Fish (Gambusia affnis), 2320 ppm
- Water fleas (Daphnia magna), 247 ppm
- Snail eggs (Lymnea), 632 ppm
- Amphipoda, 160 ppm

Environmental Fate: not persistent in aquatic systems. High pH acutely toxic to aquatic life. Does not bioaccumulate or bioconcentrate up the food chain

Potassium Chloride:

Not subject to further degradation processes in the environment. In soil, transport / leaching of potassium and chloride is affected by type of soil, pH and organic matter.

 $LC_{50};\ Species:\ Daphnia\ magna\ (Water\ flea);\ Conditions:\ freshwater;\ static;\ Concentration:\ 29\ mg/L\ for\ 96\ hr\ /total)$

LC₅₀; Species: Oncorhynchus mykiss (Rainbow trout, donaldson trout, wt 0.8-1.2 g); Conditions: freshwater; static;

Concentration: 1610 mg/L (95% confidence limit: 1223 - 2119 m/L) for 48 hr /total

LC₅₀; Species: Gambusia affinis (Western mosquitofish, female); Conditions: freshwater; static; Concentration: 435 mg/L for 96 hr /total

| Bioaccumulation | Not applicable - inorganic product | |
|-----------------------|--|--|
| Other adverse effects | The high pH of this material can be acutely toxic to the aquatic environment | |

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of this product and / or its container in accordance with Federal, state, provincial, and local regulations. Do not allow product to enter sewers or the environment.

SECTION 14: TRANSPORT INFORMATION

| CHIDDING | TDG | Not a dangerous good for transport |
|----------|-----|------------------------------------|
| SHIPPING | DOT | Not a dangerous good for transport |

SECTION 15: REGULATORY INFORMATION

This product has been classified in accordance with WHMIS 2015 and OSHA HazCom 2012

DSL: all components of this product are on Canada's DSL list

TSCA: all components of this product are on US EPA's TSCA Chemical Substances Inventory

SECTION 16: OTHER INFORMATION

As of the date of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable laws. However, no warranty or representation of law or fact, with respect to such Information is intended or given

Version 1, Print date: June 1st 2015